



Washout processor for solvent flexo plates

INCREMENTAL PROCESSOR

- . Incremental processing of flexo plates
- . Competitive washout speed and productivity
- . 2 pre-wash brushes alternate rotating and oscillating
- . 10 wash brushes alternate rotating and oscillating
- . 1 top cleaning brush, 1 top wiping brush, 2 back cleaning brushes
- . Servo drive motors for brushing system
- . 3D Brush Motion - brush speed adjusted to plate transfer speed
- . Very smooth brush start movement
- . Integrated automatic punch
- . Dual tank for digital mask separation
- . Automatic solvent pollution measurement and replenishment
- . Tilting and rotating screen display
- . Integrated flowmeter for fresh solvent inlet, value on screen
- . Integrated heating/chilling unit for uniform solvent temperature
- . 8 pin bars holder, plate holder on input
- . possible to integrate Light Finisher under exit table, left or right side.
- . remote internet connection for diagnostics and on-line support

TECHNICAL DATA :

Dimensions (WxLxH)

529 x 220 x 110 cm (208 x 86 x 43 inch)

Weight

1 700 kg / 3 748 pounds

Power supply

400V 3PH/N/PE 50/60Hz 9Kw 15A
230V 3PH/PE 50/60Hz 9Kw 26A

Maximum plate size

1 320 x 2 032 mm (52 x 80 inch)

Minimum plate size

200 x 200 mm (8 x 8 inch)

Plate thickness

Up to 7 mm / 0.276 inch

Compressed air supply

min. 6 bar